

ROLLER BALL LOCK TYPE CABLE TIES

COATED



Technical Specifications

Material	304 and 316L grade non-magnetic stainless steel
Temperature Range	-60 C to +150°C
Surface Finish	Epoxy/Polyester Coated
Flamability Rating	UL94 Fireproof & UV Resistant



Part Code as per Stainless Steel Grade		Width		Length		Thickness		Max. Loop Diameter		Max. Loop Tensile Strength		Package Quantity
SS304	SS316L	Inch	mm	Inch	mm	Inch	mm	Inch	mm	N	lbs	Pcs
CBC14-100	CBC16-100	0.18	4.6	4	100	0.01	0.25	0.94	24	465	105	100
CBC14-127	CBC16-127	0.18	4.6	5	127	0.01	0.25	1.02	26			
CBC14-150	CBC16-150	0.18	4.6	6	150	0.01	0.25	1.57	40			
CBC14-200	CBC16-200	0.18	4.6	8	200	0.01	0.25	2.20	56			
CBC14-260	CBC16-260	0.18	4.6	10	260	0.01	0.25	2.95	75			
CBC14-300	CBC16-300	0.18	4.6	12	300	0.01	0.25	3.46	88			
CBC14-360	CBC16-360	0.18	4.6	14	360	0.01	0.25	4.21	107			
CBC14-400	CBC16-400	0.18	4.6	16	400	0.01	0.25	4.53	115			
CBC14-450	CBC16-450	0.18	4.6	18	450	0.01	0.25	5.31	135			
CBC14-520	CBC16-520	0.18	4.6	20	520	0.01	0.25	6.22	158			
CBC14-550	CBC16-550	0.18	4.6	22	550	0.01	0.25	6.38	162			
CBC14-620	CBC16-620	0.18	4.6	24	620	0.01	0.25	7.48	190			
CBC14-680	CBC16-680	0.18	4.6	27	680	0.01	0.25	7.87	200			
CBC14-840	CBC16-840	0.18	4.6	33	840	0.01	0.25	10.24	260			
CBC14-1000	CBC16-1000	0.18	4.6	39	1000	0.01	0.25	12.24	311			

Part Code as per Stainless Steel Grade		Width		Length		Thickness		Max. Loop Diameter		Max. Loop Tensile Strength		Package Quantity
SS304	SS316L	Inch	mm	Inch	mm	Inch	mm	Inch	mm	N	lbs	Pcs
CBC24-100	CBC26-100	0.31	7.9	4	100	0.01	0.25	0.94	24	1200	270	100
CBC24-127	CBC26-127	0.31	7.9	5	127	0.01	0.25	1.02	26			
CBC24-150	CBC26-150	0.31	7.9	6	150	0.01	0.25	1.57	40			
CBC24-200	CBC26-200	0.31	7.9	8	200	0.01	0.25	2.20	56			
CBC24-260	CBC26-260	0.31	7.9	10	260	0.01	0.25	2.95	75			
CBC24-300	CBC26-300	0.31	7.9	12	300	0.01	0.25	3.46	88			
CBC24-360	CBC26-360	0.31	7.9	14	360	0.01	0.25	4.21	107			
CBC24-400	CBC26-400	0.31	7.9	16	400	0.01	0.25	4.53	115			
CBC24-450	CBC26-450	0.31	7.9	18	450	0.01	0.25	5.31	135			
CBC24-520	CBC26-520	0.31	7.9	20	520	0.01	0.25	6.22	158			
CBC24-550	CBC26-550	0.31	7.9	22	550	0.01	0.25	6.38	162			
CBC24-620	CBC26-620	0.31	7.9	24	620	0.01	0.25	7.48	190			
CBC24-680	CBC26-680	0.31	7.9	27	680	0.01	0.25	7.87	200			
CBC24-840	CBC26-840	0.31	7.9	33	840	0.01	0.25	10.24	260			
CBC24-1000	CBC26-1000	0.31	7.9	39	1000	0.01	0.25	12.24	311			

Part Code as per Stainless Steel Grade		Width		Length		Thickness		Max. Loop Diameter		Max. Loop Tensile Strength		Package Quantity
SS304	SS316L	Inch	mm	Inch	mm	Inch	mm	Inch	mm	N	lbs	Pcs
CBC34-100	CBC36-100	0.5	12	4	100	0.01	0.25	0.94	24	2000	450	100
CBC34-127	CBC36-127	0.5	12	5	127	0.01	0.25	1.02	26			
CBC34-150	CBC36-150	0.5	12	6	150	0.01	0.25	1.57	40			
CBC34-200	CBC36-200	0.5	12	8	200	0.01	0.25	2.20	56			
CBC34-260	CBC36-260	0.5	12	10	260	0.01	0.25	2.95	75			
CBC34-300	CBC36-300	0.5	12	12	300	0.01	0.25	3.46	88			
CBC34-360	CBC36-360	0.5	12	14	360	0.01	0.25	4.21	107			
CBC34-400	CBC36-400	0.5	12	16	400	0.01	0.25	4.53	115			
CBC34-450	CBC36-450	0.5	12	18	450	0.01	0.25	5.31	135			
CBC34-520	CBC36-520	0.5	12	20	520	0.01	0.25	6.22	158			
CBC34-550	CBC36-550	0.5	12	22	550	0.01	0.25	6.38	162			
CBC34-620	CBC36-620	0.5	12	24	620	0.01	0.25	7.48	190			
CBC34-680	CBC36-680	0.5	12	27	680	0.01	0.25	7.87	200			
CBC34-840	CBC36-840	0.5	12	33	840	0.01	0.25	10.24	260			
CBC34-1000	CBC36-1000	0.5	12	39	1000	0.01	0.25	12.24	311			

***Available in Multicolor Options.**