

BANDS



HF Halogen
FREE

Technical Specifications

Material	SS 201, SS 304 & SS 316
Temperature Range	-60° C to +300°C (Uncoated) -60° C to +150°C (Coated)
Surface Finish	Coated/Uncoated
Flamability Rating	UL 94 Fireproof & UV Resistant



Part Code as per Stainless Steel Grade			Width		Thickness		Finished Length		Average Breaking Strength						Package
									SS201		SS304		SS316		
SS201	SS304	SS316L	Inch	mm	Inch	mm	Inch	mm	N	lbs	N	lbs	N	lbs	Pcs
CSU1-1X30	CSU4-1X30	CSU6-1X30	1/4	6.5	0.020	0.5	100	30.5	2225	500	1669	375	1780	400	100'/Roll
CSU1-2Y30	CSU4-2Y30	CSU6-2Y30	3/8	9.5	0.026	0.65	100	30.5	4005	900	3115	700	3338	750	100'/Roll
CSU1-3Z30	CSU4-3Z30	CSU6-3Z30	1/2	12.7	0.030	0.75	100	30.5	6675	1500	4895	1100	5340	1200	100'/Roll
CSU1-4Z30	CSU4-4Z30	CSU6-4Z30	5/8	16	0.030	0.75	100	30.5	8345	1875	6230	1400	6675	1500	100'/Roll
CSU1-5Z30	CSU4-5Z30	CSU6-5Z30	3/4	19	0.030	0.75	100	30.5	10015	2250	7395	1700	8010	1800	100'/Roll
NA	CSP4-1X30	CSP6-1X30	1/4	6.5	0.020	0.5	100	30.5	NA	NA	1490	335	1490	335	100'/Roll
NA	CSP4-2Y30	CSP6-2Y30	3/8	9.5	0.026	0.65	100	30.5	NA	NA	2250	505	2250	505	100'/Roll
NA	CSP4-3Z30	CSP6-3Z30	1/2	12.7	0.030	0.75	100	30.5	NA	NA	2980	670	2980	670	100'/Roll
NA	CSP4-4Z30	CSP6-4Z30	5/8	16	0.030	0.75	100	30.5	NA	NA	3740	840	3740	840	100'/Roll
NA	CSP4-5Z30	CSP6-5Z30	3/4	19	0.030	0.75	100	30.5	NA	NA	4450	1000	4450	1000	100'/Roll

NOMENCLATURE

PRODUCT TYPE: ES/EA

SURFACE FINISH: U/C/P

MATERIAL GRADE: 1/4/6/G

WIDTH: 1/2/3/4/5

THICKNESS: X/Y/Z

STRAP LENGTH: xx

**ES: STRAP
EA: ALL PURPOSE BANDS**

**U: UNCOATED
C: EPOXY/POLYESTER COATED
P: PPA 571 COATED**

**1: SS 201 / 4: SS 304
6: SS 316 / G: GCS**

**1: 6.5mm / 2: 9.5mm
3: 12.7mm / 4: 16mm / 5: 19mm**

**X: 0.50mm / Y: 0.65mm
Z: 0.75mm**

xx: 3, 10, 25, 30.5, 50, 61

ALL PURPOSE BANDS



Technical Specifications

Material	SS 304, SS 316 & Galvanised Carbon Steel (GCS)
Temperature Range	-60° C to +300°C (Uncoated) -60° C to +150°C (Coated)
Surface Finish	Coated/Uncoated
Flamability Rating	UL 94 Fireproof & UV Resistant



UNCOATED

Part Code as per Stainless Steel Grade			Width		Thickness		Finished Length		Dimater of Hole		Package Quantity
GCS	SS304	SS316L	Inch	mm	Inch	mm	feet	Mtr	Inch	mm	Pcs
CAUG-3Z03	CAU4-3Z03	CAU6-3Z03	1/2	12.7	0.03	0.75	9.9	3	1/5	5	9.9'/Roll
CAUG-3Z10	CAU4-3Z10	CAU6-3Z10	1/2	12.7	0.03	0.75	33.0	10	1/5	5	33'/Roll
CAUG-3Z25	CAU4-3Z25	CAU6-3Z25	1/2	12.7	0.03	0.75	82.5	25	1/5	5	82.5'/Roll
CAUG-5Z03	CAU4-5Z03	CAU6-5Z03	3/4	19	0.03	0.75	9.9	3	2/7	7	9.9'/Roll
CAUG-5Z10	CAU4-5Z10	CAU6-5Z10	3/4	19	0.03	0.75	33.0	10	2/7	7	33'/Roll
CAUG-5Z25	CAU4-5Z25	CAU6-5Z25	3/4	19	0.03	0.75	82.5	25	2/7	7	82.5'/Roll

COATED

Part Code as per Stainless Steel Grade			Width		Thickness		Finished Length		Dimater of Hole		Package Quantity
GCS	SS304	SS316L	Inch	mm	Inch	mm	feet	Mtr	Inch	mm	Pcs
CAPG-3Z03	CAP4-3Z03	CAP6-3Z03	1/2	12.7	0.03	0.75	9.9	3	1/5	5	9.9'/Roll
CAPG-3Z10	CAP4-3Z10	CAP6-3Z10	1/2	12.7	0.03	0.75	33.0	10	1/5	5	33'/Roll
CAPG-3Z25	CAP4-3Z25	CAP6-3Z25	1/2	12.7	0.03	0.75	82.5	25	1/5	5	82.5'/Roll
CAPG-5Z03	CAP4-5Z03	CAP6-5Z03	3/4	19	0.03	0.75	9.9	3	2/7	7	9.9'/Roll
CAPG-5Z10	CAP4-5Z10	CAP6-5Z10	3/4	19	0.03	0.75	33.0	10	2/7	7	33'/Roll
CAPG-5Z25	CAP4-5Z25	CAP6-5Z25	3/4	19	0.03	0.75	82.5	25	2/7	7	82.5'/Roll

BUCKLES



HF Halogen
FREE

Technical Specifications

Material	SS 201, Ss304 & Ss316
Temperature Range	-60° C to +300°C (Uncoated) -60° C to +150°C (Coated)
Surface Finish	Coated/Uncoated
Flamability Rating	UL 94 Fireproof & UV Resistant



Part Code as per Stainless Steel Grade			Width		Package Quantity
SS201	SS304	SS316L	Inch	mm	Pcs
CJU1-06	CJU4-06	CJU6-06	1/4	6.5	100
CJU1-09	CJU4-09	CJU6-09	3/8	9.5	100
CJU1-12	CJU4-12	CJU6-12	1/2	12.7	100
CJU1-16	CJU4-16	CJU6-16	5/8	16	100
CJU1-19	CJU4-19	CJU6-19	3/4	19	100

Part Code as per Stainless Steel Grade			Width		Package Quantity
SS201	SS304	SS316L	Inch	mm	Pcs
CJC1-06	CJC4-06	CJC6-06	1/4	6.5	100
CJC1-09	CJC4-09	CJC6-09	3/8	9.5	100
CJC1-12	CJC4-12	CJC6-12	1/2	12.7	100
CJC1-16	CJC4-16	CJC6-16	5/8	16	100
CJC1-19	CJC4-19	CJC6-19	3/4	19	100

Part Code as per Stainless Steel Grade			Width		Package Quantity
SS201	SS304	SS316L	Inch	mm	Pcs
CWU1-06	CWU4-06	CWU6-06	1/4	6.5	100
CWU1-09	CWU4-09	CWU6-09	3/8	9.5	100
CWU1-12	CWU4-12	CWU6-12	1/2	12.7	100
CWU1-16	CWU4-16	CWU6-16	5/8	16	100
CWU1-19	CWU4-19	CWU6-19	3/4	19	100

Part Code as per Stainless Steel Grade			Width		Package Quantity
SS201	SS304	SS316L	Inch	mm	Pcs
CWC1-06	CWC4-06	CWC6-06	1/4	6.5	100
CWC1-09	CWC4-09	CWC6-09	3/8	9.5	100
CWC1-12	CWC4-12	CWC6-12	1/2	12.7	100
CWC1-16	CWC4-16	CWC6-16	5/8	16	100
CWC1-19	CWC4-19	CWC6-19	3/4	19	100

