

CABLE MARKER TAGS & CARRIER STRIPS



Technical Specifications

Material	316L grade non-magnetic stainless steel
Temperature Range	-60° C to +350°C
Surface Finish	Metallic & Epoxy / Polyester Coating (Carrier Strip)
Flamability Rating	UL 94 Fireproof & UV Resistant



Part Code as per Stainless Steel Grade	Width		Length		Thickness		Package Qty	Product Design
	Inch	mm	Inch	mm	Inch	mm		
SS316							Pcs	
CT7407/0.50	2/7	7	3	74	0.020	0.5	100	
CT8909/0.50	3/8	9.5	3 1/2	89	0.020	0.5		
CT8909/0.30	3/8	9.5	3 1/2	89	0.012	0.3		
CT8919/0.50	3/4	19	3 1/2	89	0.020	0.5		
CT8919/0.25	3/4	19	3 1/2	89	0.010	0.25		
CTS8919/0.50	3/4	19	3 1/2	89	0.020	0.5		
CTCP8919/0.50	3/4	19	3 1/2	89	0.020	0.5		
CT6338/0.50	1 1/2	38	2 1/2	63	0.020	0.5		

Part Code as per Stainless Steel Grade		Width		Length		Thickness		Package Qty
Uncoated	Coated	Inch	mm	Inch	mm	Inch	mm	
UNID 6	CNIDC 6	1/3	8	3 2/3	92.5	0.020	0.5	100
UNID 10	CNIDC 10	1/3	8	5 2/9	132.5	0.020	0.5	
UNID 12	CNIDC 12	1/3	8	6	152.5	0.020	0.5	
UNID 16	CNIDC 16	1/3	8	7 4/7	192.5	0.020	0.5	
UNID 22	CNIDC 22	1/3	8	10	252.5	0.020	0.5	

