MECHANICAL CONNECTORS

CIMC & CIMCN









INSERTS

Lugs and connectors are provided with inserts for smaller conductors. These inserts have lengthwise serrations and a positioning guide.

TYPES OF MECHANICAL CONNECTORS & LUGS

CIMC- Mechanical Connectors - Block

CIMCN - Mechanical Connectors - No Block

CIML- Mechanical Lugs

CIMLC- Mechanical Lugs Center Palm

CILTMC- Low Tension Mechanical Connectors

CIRBC- Reducer type Bolted Connector

Chamfered edges Suitable for up to 42 kV and adaptable to existing joint designs Available with and without oil barrier, oil stop when used in transition joints

Long shank, Extra-long for moisture barrier Lengthwise seal for indoor and outdoor applications

EMC, Mechanical connectors, Mechanical Lugs and repair sleeves are designed for use in low and medium voltage applications.

Four sizes of our EMC connectors cover conductors' sizes ranging from 25 mm2 to 630 mm2. Our connectors consist of a tin-plated body, shear bolt heads and inserts for small conductor


Made of special aluminium alloy, these contact bolts are double shear bolt heads with hexagon heads. The bolts are treated with a highly lubricating agent.

Contact bolts are irremovable once their heads have been sheared off. The internal surface of the conductor holes are grooved.

The connectors are chamfered at the edges and available with or without oil barrier (as blocked and unblocked types) depending on the application requirements.

The bolted fitting featured herein was developed specifically for use in medium voltage cable accessories up to 42 kV





| CABLE SIZE MM2 | DIMENSIONS MM | | | | | NUMBE | HEAD SIZE | PRODUCT | CANDOUR |
|----------------|---------------|------|-----|----|------|---------------|-----------|----------------|-----------|
| | BLOCKE D | L | В | С | A | R OF BOLTS | AF MM | CODE | ITEM CODE |
| 25-95 | YES | - 65 | 30 | 24 | 12.8 | 2 | 13 | CI-MC 25-95 | 83000000 |
| | NO | | | | | | | CI-MCN 25-95 | 83000001 |
| 35-150 | YES | 80 | 38 | 28 | 15.8 | 2 | 17 | CI-MC 35-150 | 83000002 |
| | NO | | | | | | | CI-MCN 35-150 | 83000003 |
| 95-240 | YES | 125 | 60 | 33 | 20 | 4 | 19 | CI-MC 95-240 | 83000004 |
| | NO | | | | | | | CI-MCN 95-240 | 83000005 |
| 120-300 | YES | 140 | 68 | 37 | 24.0 | 4 | 22 | CI-MC 120-300 | 83000006 |
| | NO | | | | | | | CI-MCN 120-300 | 83000007 |
| 185-400 | YES | 170 | 83 | 42 | 25.5 | 6 | 22 | CI-MC 185-400 | 83000008 |
| | No | | | | | | | CI-MCN 185-400 | 83000009 |
| 500 | YES | 160 | 75 | 46 | 29.6 | 6 | 13 | CI-MC 500 | 83000010 |
| 630 | YES | 160 | 75 | 50 | 33 | 6 | 13 | CI-MC 630 | 83000011 |
| 800 | YES | 220 | 105 | 56 | 36 | 6 | 27 | CI-MC 800 | 83000012 |



